

Based Upon: PCT/EP2005/006594

### REMARKS

Applicant respectfully requests entry of the above Preliminary Amendment to place this U.S. Patent Application in better form for examination and prosecution before the U.S. Patent and Trademark Office.

The claims have been amended to eliminate multiple dependent claims and to more definitely and fully claim the subject matter of Applicant's invention. Applicant urges that the above Preliminary Amendment introduces no new matter into this U.S. Patent Application.

Applicant sincerely believes that this U.S. Patent Application is now in condition for examination and prosecution before the U.S. Patent and Trademark Office.

Respectfully submitted,



Douglas H. Pauley  
Registration No. 33,295

Pauley Petersen & Erickson  
2800 West Higgins Road; Suite 365  
Hoffman Estates, Illinois 60195  
TEL (847) 490-1400  
FAX (847) 490-1403

10/576379

IAP20 Rec'd PCT/PTO 19 APR 2006

WO 2006/007913  
PCT/EP2005/006594BACKGROUND OF THE INVENTION  
Field of the Invention

## Bus Bar Support

[The] <sup>This</sup> invention relates to a bus bar support, having a lower element, which can be mounted with its underside on a base, [on whose] <sup>a</sup> top <sup>into which</sup> several bus bar receptacles [have been] <sup>are</sup> cut, which are <sup>and</sup> spaced apart <sup>from</sup> [from] each other in the longitudinal direction and are designed for the insulated insertion of bus bars extending in [the] <sup>a</sup> transverse direction, and a removable upper element, which closes the receptacles and fixes the inserted bus bars in place.

[Such a] <sup>A</sup> bus bar support is <sup>Discussion of Related Art</sup> represented in (non-published) <sup>taught by German Patent Reference</sup> DE 103 00 723 A1. With this known bus bar support <sup>is</sup> of a bus bar system, <sup>several</sup> several bus bars [have been] <sup>are</sup> inserted in a customary manner into rectangular, open at the top, receptacles on a lower element, [whose] <sup>with a</sup> longitudinal direction <sup>that</sup> is oriented transversely <sup>in</sup> [in] <sup>with</sup> respect to the bus bars, and are fixed in place therein [by means of] an upper element screwed to it. The underside of the lower element is mounted on a base. If it is necessary to fix bus bars of different width or thickness in this way, [it is necessary to employ] bus bar supports with appropriately matched bus bar receptacles. <sup>are used</sup>

[The] <sup>One</sup> object of [the] <sup>this SUMMARY OF THE INVENTION</sup> invention is <sup>to provide</sup> based on making available <sup>a</sup> a bus bar support of the type mentioned [at the outset, by means of] <sup>above but in</sup> which bus bars of different width and thickness can be solidly fixed in place.

This object is attained [by means of] <sup>with a bus bar support having</sup> the characteristics [of claim 1]. <sup>There are</sup> [It is provided here that] separate sliding elements [are provided] for blocking the bus bar receptacles in a direction of their thickness extending from the bottom to the top, and bearing inserts for blocking the bus bar receptacles in a direction extending transversely to the

described in this specification  
and in the claims

WO 2006/007913  
PCT/EP2005/006594

longitudinal extension of inserted bus bars and in the longitudinal direction of the lower element, and that in its areas surrounding the bus bar receptacles, the bus bar support <sup>has</sup> [is provided with] guide structures, in which the sliding elements and the bearing inserts are displaceably seated. <sup>In</sup>

Variable matching of the bus bar receptacle to bus bars of different width and/or thickness is possible [by means of] with the sliding elements and bearing inserts seated in this way, while providing solid fixation in place, wherein it is also possible to insert into the bus bar receptacles of the bus bar support, for example, bus bars which are of different width or thickness from one bus bar receptacle to the other bus bar receptacle of the same support. <sup>It</sup>

Simple handling and adaptation to common bus bar cross sections <sup>are</sup> [is] achieved [in that] if the bus bar receptacles have a rectangular shape in longitudinal section of the lower element and are open toward the top, that in their blocking position, the sliding elements rest on the underside of the bus bar receptacle and [that] in their blocking position the bearing inserts rest against a lateral face of the bus bar receptacle. <sup>In</sup>

[A] <sup>In a</sup> simple embodiment which [makes possible] <sup>provides</sup> simple manipulation when matching the thickness, [consists in that] the sliding elements are designed to be U-shaped and [that] the guide structures for the sliding elements are embodied as guide grooves, which extend from a lateral surface of the bus bar receptacle parallel with the base of the bus bar receptacle and in which the lateral legs are guided [wherein, in the pushed-out position, the bottom of the U rests with its underside on the base of the bus bar receptacle. <sup>In</sup>

WO 2006/007913  
PCT/EP2005/006594

Definite positions of the sliding element are obtained <sup>having</sup> with [in that its] resiliently designed lateral legs [are provided] on their inside [with] snap-in elements, and at least one snap-in counter element, which is matched to them, is embodied in the guide grooves and arranged [in such a way] <sup>so</sup> that, in the completely inserted position of the sliding element and/or in the pulled-out position of the sliding element, the lateral legs are resiliently snapped in <sup>place. On</sup> and that, on the guide face of the bus bar receptacles adjoining the guide grooves, a transversely extending cutout which [has been] <sup>is</sup> matched to the bottom of the U [has been] <sup>is</sup> cut, into which the bottom of the U completely enters in the completely pushed-in state of the sliding element, so that the entire depth of the bus bar receptacle is usable. These measures also contribute to the captive seating of the sliding elements on the lower element [wherein it can be provided that, if] <sup>if</sup> required, the sliding elements can be completely removed over a detent in the groove by the exertion of additional force. [With this embodiment it is also assured that] <sup>Thus,</sup> in the completely pushed-in state of the sliding elements the sliding element receiver is available over its entire thickness.

A simple adaptation to different bus bar widths, along with a simple manipulation, is achieved by [means of] the steps wherein insert guides are formed below the bus bar receptacles between lateral outside wall areas of the lower element, in which bearing inserts are seated, displaceable to a limited extent in the direction of the normal line [in] <sup>with</sup> respect to the bottom of the bus bar receptacle [wherein, in]. In the completely lowered state, the bearing inserts reach with their tops at most as far as the bottom of the bus bar receptacle, and in their blocking position rest with their

WO 2006/007913  
PCT/EP2005/006594

backs on the lateral surface of the bus bar receptacle located opposite the sliding element, and the <sup>the</sup> clear width of the bus bar receptacles is limited by a front of the bearing insert which is definitely distanced parallel from this lateral surface.

If [it is provided that] the fronts of the bearing inserts are [embodied to be] stepped, so that several front sections are formed, which definitely limit the bus bar receptacles in the broad direction as a function of the number of steps, [i.e.] <sup>such as</sup> the number of front sections formed by them, <sup>then there are</sup> a corresponding multitude of adaptations to different bus bars widths [results]. In this way, a match to a multitude of bus bars with different cross sections in the thickness and width directions results in combination with the separate sliding element.

Handling is [furthermore made easier in that] <sup>simplified if</sup> the bearing inserts are supported by [means of] a spring arrangement in the respective insert guides, and in the position of rest are pushed out into the bus bar receptacle as far as their push-in limit. [In the course of] <sup>while</sup> inserting the bus bars, the bearing inserts are pushed in against the spring force if required, in order to insert a wider bus bar.

[Here, an] <sup>In one</sup> embodiment which is advantageous for the structure and the way of functioning, [consists in that] the spring arrangement has a compression spring, which is supported on a support element which is releasably inserted in the area of the underside of the lower element. [Moreover] <sup>Also</sup> those measures are advantageous for the production and the structure of the bus bar support, wherein on two oppositely located outer edges the support element [is provided with] <sup>has</sup> fixation sections, [ ] which [have been] <sup>are</sup> snapped into matched

WO 2006/007913  
PCT/EP2005/006594

an exploded perspective view  
of a bus bar support with a  
lower element, according to  
one embodiment of this invention.

fixation elements on the outside wall areas of the lower  
element.

# BRIEF DESCRIPTION OF THE DRAWING

<sup>This</sup> [The] invention [will be] explained in greater detail in  
<sup>view</sup> [what follows by means] of an exemplary embodiment, making  
reference to the drawings [is], wherein the figure shows

The [drawing] figure shows a bus bar support with a lower  
element 2, which can be mounted with its underside on a base  
and in whose top, which faces away from the underside,  
several, in this case three, bus bar receptacles 2.3 [have  
been] <sup>are</sup> formed, in which bus bars, in particular of rectangular  
cross section, can be received, which are <sup>and</sup> fixed in place by  
[means of] an upper element 1, which is <sup>and fixed</sup> to be screwed on or  
snapped on. For screwing, the upper element 1 has screw  
holes 1.1, which correspond to screw receivers 2.1 in the  
lower element 2.

The bus bar receptacles 2.3 can be varied in their  
thickness <sup>or</sup> [depth] and their width extending in the  
longitudinal direction of the lower element 2 by [means of]  
inserted sliding elements 3 in order to provide an adaptation  
to bus bars of different width and/or thickness. For  
inserting the sliding element 3, guide grooves 2.2, which are  
U-shaped in cross section, [have been] <sup>are</sup> cut parallel with the  
underside of the bus bar receptacle 2.3 on both outer sides  
of the lower element 2 into a lateral wall which delimits the  
bus bar receptacle 2.3 in the direction of its width, <sup>and</sup> whose  
underside [extends in the present case] <sup>can extend</sup> flush with the  
underside of the bus bar receptacle 2.3, and whose width is  
matched to the thickness of the sliding elements 3 extending  
in the direction of the depth of the bus bar receptacle 2.3  
wherein the <sup>The</sup> lateral legs 3.1 of the U-shaped sliding elements  
3 are displaceably guided in the guide grooves 2.2. In the

WO 2006/007913  
PCT/EP2005/006594

end area located toward the bus bar receptacle 2.3 of the groove bottom of the guide grooves 2.2 and in their end area facing away from the bus bar receptacle 2.3, holding elements 2.21 in the form of recesses ~~[have been]~~<sup>are</sup> formed, into which snap-in protrusions 3.2 formed on the end areas of the insides of the lateral legs snap in by ~~[means of]~~ the spring effect of the lateral legs 3.1 when the respective sliding element 3 ~~[has been]~~<sup>is</sup> completely pushed in, or ~~[has been]~~<sup>is</sup> brought into the pulled-out position. <sup>Also</sup> ~~[Moreover]~~, in the completely pushed-in position, the bottom of the U of the sliding element 3 rests completely in a recess 2.7 formed in the assigned lateral face of the bus bar receptacle 2.3 between the two respective guide grooves 2.2, so that the entire depth of the bus bar receptacle 2.3 is available without limitation. In the pulled-out state of the sliding elements 3 these rest with ~~[the]~~<sup>an</sup> underside of their lateral legs 2.1 and its bottom of the U on the underside of the bus bar receptacle 2.3, so that the bus bar receptacle 2.3 is accordingly limited in its depth and an inserted bus bar is solidly supported on the lower element 2. On their exterior, the lateral legs 3.1 have ~~[been provided with]~~ a non-skid structure, so that they can be easily adjusted. It is also advantageous ~~[that]~~<sup>if</sup> the sliding elements 3 are captively held in the guide grooves 2.2 of the lower element 2.

For varying the width of the bus bar receptacles 2.3, displaceable bearing inserts 4 are provided in the direction of thickness of the bus bar, or the direction of depth of the bus bar receptacle 2.3, which are displaceably seated in an insert guide 2.4 arranged between outside wall areas of the lower element 2. In their state in which they ~~[have been]~~<sup>are</sup> pushed out toward the top, in which they delimit the

WO 2006/007913  
PCT/EP2005/006594

respective bus bar receptacle 2.3 in the direction of width by [means of] their front side facing the receptacle, the bearing inserts 4 rest with their backs against the respective lateral face of the bus bar receptacle 2.3 which faces away from the sliding element 3, so that a solid support in the direction of width results. On their front facing the clear space of the bus bar receptacle 2.3, the bearing inserts have front sections formed by [means of] steps 4.1, which extend parallel [in] <sup>with</sup> respect to the lateral surface of the bus bar receptacle 2.3. [In this way, <sup>thus</sup> depending on the push-out distance of the bearing inserts 4 from the insert guide 2.4, different widths of the bus bar receptacle 2.3 are achieved, so that differently wide bus bars can be solidly fixed in place accordingly.

Toward the bottom, the bearing inserts 4 are supported by [means of] respective compression springs 5 on a support element 6, which [has been] <sup>is</sup> fixed in place in the area of the underside of the lower element 2. The plate-shaped support element 6 has a holding peg 6.2, which is formed on its top and matched to the cylindrical spring 5 for inserting the spring 5. With its other end, the spring 5 is definitely maintained in the area of the underside, or inside, of the bearing insert 4 at a matched holding element. So that the bearing insert 4 is definitely guided in the direction of the thickness of the bus bar, guide grooves which extend in the thickness direction [have been] <sup>are</sup> cut on both sides of it, which are engaged by guide elements 2.6 in the form of guide strips formed on the inside of the outside wall sections. In the completely pushed-in position, the bearing insert 4 protrudes with its top at most as far as the level of the underside of the bus bar receptacle 2.3. The pushed-out position of the



WO 2006/007913  
PCT/EP2005/006594

bearing insert 4 is delimited by (means of) a blocking element 4.3, which works together with a blocking element attached at a corresponding location of the lower element 2.

[By means of] <sup>With</sup> fixation sections 6.1 in the shape of snap-in pegs and snap-in protrusions attached on the inside in the lower area of the outside wall sections to both sides of the support element 6, the [latter has been] <sup>support element 6 is</sup> solidly and releasably snapped into fixation elements 2.5 in the shape of snap-in recesses applied to the appropriate locations and for supporting the spring 5.

The sliding element 3 and the bearing inserts 4, which can be adjusted separately [of the former], <sup>simply</sup> permit the matching of the bus bar receptacle 2.3 to bus bars of different thickness and different width [in a simple way], wherein the adjustment elements in the form of the sliding elements and bearing inserts 4 are captively held in the lower element 2. For inserting a bus bar, first the sliding element 3 is placed into the pushed-in or pulled-out position corresponding to the thickness of the bus bar, [whereafter] <sup>then</sup> the underside of the bus bar is introduced into the bus bar receptacle 2.3, wherein the one narrow longitudinal side is placed against the lateral surface of the bus bar receptacle facing the sliding element 3, so that the other narrow longitudinal side automatically finds the appropriate front section of the bearing insert 4 for blocking, and the bearing insert 4, if required, is then inserted accordingly far into the insert guide 2.4 against the spring force.

It is advantageous to match the bus bar receptacle 2.3, the slider 3 and the bearing inserts 4 in accordance with common cross-sectional dimensions of bus bars, for example 15x5 to 30x10 mm, in steps of 5 mm in thickness and width.

WO 2006/007913  
PCT/EP2005/006594

In this case bus bars with cross sections which differ from each other can then also be inserted into the different bus bar receptacles 2.3.